

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: SAWDY, Michael Barry

SERIAL NO.: 10/533,933

ART UNIT: 3636

FILED: October 31, 2005

EXAMINER: Nelson Jr, M.

TITLE: VEHICLE FITTING

Amendment A: CLAIM AMENDMENTS

Claims 1 - 24 (canceled).

25. (new) A fitting assembly for a motor vehicle comprising:

a support frame suitable for securement to a floor of the motor vehicle;

a seat squab affixed to said support frame;

a seat back mounting affixed to said support frame;

a backrest interconnected to said support frame, said backrest having a guide at a top thereof, said seat squab being moveable between a first position in which said seat squab projects forwardly from said support frame and a second position in which seat squab does not obstruct a space in front of said backrest;

a mounting means connecting said backrest to said seat back mounting, said mounting means for enabling said backrest to move from a rearward position to a forward position in which said backrest is moved forwardly so as to be spaced from said seat back mounting; and

at least one seat belt connected to said support frame, said seat belt passing through said guide.

26. (new) The fitting assembly of Claim 25, said seat squab having a pair of mounting fingers

and a pair of mounting lugs, said support frame having a pair of formations respectively receiving said pair of mounting fingers and a pair of hooks to respectively engaging said pair of mounting lugs.

27. (new) The fitting assembly of Claim 25, said mounting means comprising a plurality of pivot links.

28. (new) The fitting assembly of Claim 27, said plurality of pivotal links comprising a pair of upper pivotal links and a pair of lower pivotal links, one of each of said pairs of upper pivotal links and lower pivotal links being affixed to said one side of adjacent seat back mounting, another of each of said pair of upper pivotal links and lower pivotal links being affixed to another side of said seat back mounting.

29. (new) The fitting assembly of Claim 27, each of said plurality of pivotal links comprising a pair of straight arms that are interconnected.

30. (new) The fitting assembly of Claim 25, said mounting means being an over-dead-center mechanism.

31. (new) The fitting assembly of Claim 30, said over-dead-center mechanism comprising:
a drive bar passing through slots formed in a pair of spaced-apart plates on said backrest, said drive bar being mounted on at least one arm which is pivotally mounted to said support frame, said drive bar movable in an arcuate pattern.

32. (new) The fitting assembly of Claim 31, further comprising:

a handle connected to the arm.

33. (new) The fitting assembly of Claim 25, further comprising:

a motor means operatively connected to said backrest for moving said backrest forwardly.

34. (new) The fitting assembly of Claim 25, said backrest pivotable about a horizontal axis when in said first position.

35. (new) A fitting assembly for a motor vehicle comprising:

a support frame suitable for securement to a floor of the motor vehicle;

a seat squab affixed to said support frame;

a seat back mounting affixed to said support frame;

a backrest interconnected to said support frame, said seat squab being moveable between a first position in which said seat squab projects forwardly from said support frame and a second position in which seat squab does not obstruct a space in front of said backrest, said support frame being mounted on rollers suitable for lateral movement.

36. (new) The fitting assembly of Claim 35, said support frame having a base plate, said fitting assembly further comprising:

a platform mounted to said base plate.

37. (new) The fitting assembly of Claim 36, said base plate having at least one projection extending downwardly therefrom, said platform having at least one channel formed therein, the projection being engaged with the channel.

38. (new) The fitting assembly of Claim 37, further comprising:

a band extending over the channel, the channel having a guide at one end thereof, said band extending from said base plate to said guide, said band passing through a passage formed under said platform.

39. (new) The fitting assembly of Claim 36, further comprising:

a clamp affixed to said base plate so as to hold said base plate in a position.

40. (new) The fitting assembly of Claim 36, further comprising:

a motor connected to said base plate for driving said base plate relative to said platform.

41. (new) The fitting assembly of Claim 35, said backrest having a wide upper portion and a narrow lower portion.

42. (new) A fitting assembly for a motor vehicle for use in association with a wheelchair comprising:

a support frame suitable for securement to a floor of the motor vehicle;

a seat back mounting affixed to said support frame, said backrest having a broad portion at a top thereof and a narrow portion at a bottom thereof so as to allow the wheelchair to be received on either side of said narrow portion, said backrest having a guide at a top thereof; and

at least one seat belt connected to said support frame, said seat belt passing hereto said guide.

43. (new) The fitting assembly of Claim 42, said backrest having an unobstructed space in a front thereof.

44. (new) The fitting assembly of Claim 42, further comprising:

a seat squab removably mounted to said support frame in a position adjacent said backrest.

45. (new) The fitting assembly of Claim 42, said seat belt comprising at least two seat belts mounted to said support frame, said guide comprising at least two guides at said top of said backrest, the seat belts respectively passing through the guides.

46. (new) The fitting assembly of Claim 42, said backrest mounted on a seat back mounting, said fitting assembly further comprising:

a means for moving said backrest forwardly from a rearward position to a forward position, said backrest being spaced from said seat back mounting in said forward position.

47. (new) The fitting assembly of Claim 46, said seat back mounting being mounted to said support frame by a yieldable connection, said yieldable connection suitable for yielding when subjected to a predetermined force.

48. (new) The fitting assembly of Claim 47, said support frame having a first torsion plate in an upper part thereof, said second torsion plate in a lower part thereof, said first and second torsion plates being interconnected so as to form said yieldable connection.